



WELL NUMBER SL-2S

SHEET 1 OF 1

PROJECT Schering Laboratories

LOCATION Moya Blvd., Stead, NV

PROJECT NUMBER 108271219

LOGGED BY J. Stimson

LOCATION
COORDINATES:
ELEVATION

DATUM

| DEPTH FEET | LAB SAMPLE | SAMPLE DEPTH | TPH-DIESEL (mg/Kg) | PID READING (ppm) | H2O LEVEL | GRAPHIC LOG | DESCRIPTION | WELL COMPLETION DETAIL |
|------------|------------|--------------|--------------------|-------------------|-----------|-------------|--|--|
| 5 | SL2S-5' | 5.0 | | 1.25 | | | 0-5': Silty gravelly sand (SM), dry, brown, silt with fine to coarse, polyimictic, poorly-sorted, subangular to subrounded sand, with gravel up to 5 mm in diameter. Crumbles with ease. | Cement seal between surface and 3'. Bentonite plug between 3 and 4'. |
| 7.0 | | | | | | | 5-13': Sandy silt with minor gravel (ML), moist, brown, fine, polyimictic, subangular, poorly-sorted sand with silt, minor gravel up to 5 mm in diameter. Crumbles with ease. | 2" SCH 40 solid PVC casing between surface and 5'. #3 sand filter pack between 4 and 30'. |
| 10 | SL2S-10' | 10.0 | | 1.00 | IV | | @12-13': first wet formation cuttings noted. | 2" SCH 40 0.02" slotted PVC screen between 5 and 30'. |
| 12.0 | | | | | | | 13-30': Silty sand (SM), wet, greenish-brown, fine, polyimictic, subangular, poorly-sorted sand with silt. Crumbles with ease. | |
| 15 | SL2S-15' | 15.0 | | 1.00 | | | | |
| 17.0 | | | | | | | | |
| 20 | SL2S-20' | 20.0 | | 1.00 | | | | |
| 22.0 | | | | | | | | |
| 25 | SL2S-25' | 25.0 | | 1.00 | | | | |
| 27.0 | | | | | | | | |
| 30 | SL2S-30' | 30.0 | | 1.25 | | | | |
| 32.0 | | | | | | | | |

DRILLING CONTRACTOR WESTEX
 HOLE DIAMETER 8.5"
 DRILLING METHOD Hollow stem auger
 DRILLING EQUIPMENT Mobile B-61 HDX
 DRILLING STARTED 10/30/95 ENDED 11/1/95

REMARKS Water level measured on 11/3/95.