WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51467
Permit No.
Basin 084

NOTICE OF INTENT NO. 26370

1. OWNER DAVID & CHERYL LEE
MAILING ADDRESS 900 KENNAL CANYON RD. SPARKS, NV. 89436
ADDRESS AT WELL LOCATION 900 KENNAL CANYON ROAD OFF OF ARCHANDLE DR.

2. LOCATION SE ¼ SW ¼ Sec. 4 T. 21N N/S R. 21 E. WASHOE County
PERMIT NO. 5277 Issued by Water Resources
-480-05 77 Parcel No.
CURNOW CANYON AREA LOT E. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
COBBLES, RED CLAY		0	80	80
BASALT-DRK GRAY		80	100	20
RED CINDER		100	115	15
BASALT-DRK GRAY	120'	115	300	185
BROKEN BASALT LT-MED GRAY.		300	400	100
BASALT-FRACTURED MED-DRK GRAY.	406'	400	460	60

Date started 3-16, 1995
Date completed 3-30, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
PAIL	24		4 HRS

8. WELL CONSTRUCTION
Depth Drilled 460 Feet Depth Cased 430 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	220 Feet
8 3/8 Inches		220 Feet	460 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+2'	430

Perforations:
Type perforation MECHANICAL SLOT
Size perforation 3/32 x 1 1/2
From 120 feet to 140 feet
From 240 feet to 260 feet
From 400 feet to 430 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 58'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 58' feet to 430 feet

9. WATER LEVEL
Static water level 120 feet below land surface
Artesian flow NONE G.P.M. — P.S.I.
Water temperature — °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name W.H. BLAWE WELL DRLG & PUMP Co. Contractor
Address 2537 LARRY CIRCLE Contractor
CARSON CITY, NV 89706
Nevada contractor's license number issued by the State Contractor's Board 10950.
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1974
Signed Jimmy Nelap By driller performing actual drilling on site or contractor
Date 5-30-95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627