Need copy

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 51522
Rec. 10-2 19.25
Well No.
Permit No. 15398
Do not fill in

Owner: Perl E. Ward
Address: Pahrump, Nev.
Driller: H. V. Weimer
Address: Box 116 Pahrump Nev. Lic. No. 171
Location of well: NE ¼ NW ¼ Sec. 24, T21 N/S, R53 E, in Nye County
or Permit No. 15389
Water will be used for: Irrigation
Total depth of well: 298'
Size of drilled hole: 18"
Weight of casing per linear foot: 42 lbs.
Thickness of casing: ¼"
Temp. of water: 65°
Diameter and length of casing: 16" O.D. 298'
(Casing 20" in diameter and under give inside diameter; casing 20" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 21'
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: Feb. 25, 1956 Date of completion of well: March 20, 1956
Type of well rig: 71 Star - cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	top soil
5	30	25	tight red soil
30	63	33	light colored sandy formation
63	120	57	clay
120	126	6	Hard shell
126	190	64	light colored clay
190	194	4	Hard shell
194	212	18	light colored sandy formation
212	240	28	reddish clay
240	245	5	Hard shell
245	298	53	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 194 to 212 ft.
Other aquifers 31-63

First water at 31 feet.

Casing perforated
from 31 to 298 ft.

Size of perforations
¼ x 8"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diameter	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16"	0	298	298	cemented from 0' to 20'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and

Signed H. V. Weimer
Well Driller

Licence No. 171

Dated March 30, 1956

(Not to be filled in by Driller)

1958 OCT 2 AM 11 26

ENGINEER
OFFICE