PZ 96-1

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51703
Permit No.
Basin 061

NOTICE OF INTENT NO. 32516

1. OWNER BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION SW ¼ NE ¼ Sec. 19 T 36 (N)S R 50 E EUREKA County
PERMIT NO. MO/441A (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CARLIN, GRAVEL		0	435	435
CARLIN, CLAY		435	505	70
GRAVELS, BEDROCK		505	540	35

NOTE: TRANSDUCERS PLACED IN HOLE - GRAVEL PACKED AND SEPERATED BY BENTONITE HOLE PLUG

Date started JANUARY 16, 19 96
Date completed JANUARY 21, 19 96

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
60		1

8. WELL CONSTRUCTION
Depth Drilled 540 Feet Depth Cased 195 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12-1/4 Inches	0 Feet	21 Feet
6-1/4 Inches	21 Feet	540 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7	20	.250	0	21
1-1/2	3	SCH 80	0	190

Perforations:
Type perforation DRILLED
Size perforation 1/8"
From 190 feet to 195 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 101
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 101 feet to 540 feet

9. WATER LEVEL
Static water level 140 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature 64 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1410

Signed JOHN VIERGUTZ John Viergutz
By driller performing actual drilling on site or contractor
Date FEBRUARY 2, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627