WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51707
Permit No.
Basin 212

NOTICE OF INTENT NO. 17554

1. OWNER Black & Veatch
MAILING ADDRESS 1900 E. Flamingo, Ste 295 Las Vegas, NV 89119
ADDRESS AT WELL LOCATION Valley View Blvd @ Mountain View Blvd.

2. LOCATION NE ¼ SE ¼ Sec. 6 T 21 ☒ S R 61 E Clark County
PERMIT NO. MO-2724A (Issued by Water Resources) | well in Road No parcel # (Parcel No.) | (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

MW-1

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	1	1
silty gravel		1	2	1
clay		2	5	3
sandy clay		5	6	1
fine sand		6	12	6
sandy clay	10	12	15	3
fine sand, sl. clay		15	20	5
sandy clay		20	24½	4½
clay		24½	29	4½
Clayey gravel		29	30	1

Date started May 21, 1996
Date completed May 22, 1996

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)
8 Inches From 0 Feet To 30 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.218	0	30

Perforations:
Type perforation factory slot
Size perforation 0.020
From 15 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal 4-13' BENTONITE
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 13 feet to 30 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name TOM HIGH (Contractor)
Address 731 PILOT RD, STE H (Contractor)
LAS VEGAS, NV 89119
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed Tom High (By driller performing actual drilling on site or contractor)
Date 6-14-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51707
Permit No.
Basin 212

NOTICE OF INTENT NO. 17554

1. OWNER Black & Veatch
MAILING ADDRESS 1900 E. Flamingo, Ste 295 Las Vegas, NV 89119
ADDRESS AT WELL LOCATION Valley View Blvd @ Mountain View Blvd.

2. LOCATION NE ¼ SE ¼ Sec. 6 T. 21 ☒ S R. 61 E. Clark County
PERMIT NO. MO-2724A (Issued by Water Resources) 162-06-699-010 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

MW-1

Material	Water Strata	From	To	Thickness
Asphalt		0	1	1
Silty gravel		1	2	1
clay		2	5	3
Sandy clay		5	6	1
fine sand		6	12	6
	10			
Sandy clay		12	15	3
fine sand, sl. clay		15	20	5
Sandy clay		20	24½	4½
Clay		24½	29	4½
Clayey gravel		29	30	1

Date started May 21, 19 96
Date completed May 22, 19 96

7. WELL TEST DATA
TEST METHOD ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
8	0	30

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.64	0.218	0	30

Perforations:
Type perforation factory slot
Size perforation 0.020
From 15 feet to 30 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal 4-13' BENTONITE
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 13 feet to 30 feet

9. WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Tom High
Address 731 Pilot Rd, Ste H (Contractor)
Las Vegas, NV 89119 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed (By driller performing actual drilling on site or contractor)
Date 6-14-96

RECEIVED JUN 20 1996

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627