96-14

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51753
Permit No.
Basin

NOTICE OF INTENT NO. 325

1. OWNER FIRST MISS GOLD CO.
MAILING ADDRESS P.O. BOX 220
GOLCONDA, NV 89414

ADDRESS AT WELL LOCATION
GETCHELL MINE SITE

2. LOCATION SE ¼ NE ¼ Sec. 33 T 39 N/S R. 42 E. HUMBOLDT County
PERMIT NO. M/O-993-A (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL, ALUVIUM		0	80	80
BASALTS		80	550	470
HORNFEL, SKARN		550	760	210
DACITE DIKE		760	780	20
SKARN		780	865	85
DACITE DIKE		865	970	105
SKARN		970	1300	330
SHALE		1300	1325	25
SKARN		1325	1355	30
GRAY SHALE		1355	1480	125
HORNFEL SKARN		1480	2315	835
DIKE		2315	2350	35
SHALE		2350	2400	50
SKARN		2400	2535	135

Date started MAY 6, 1996
Date completed MAY 8, 1996

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AIRLIFT	4-5		19 HOURS

8. WELL CONSTRUCTION
Depth Drilled 2535 Feet Depth Cased 1950 Feet

HOLE DIAMETER (BIT SIZE)

			From		To	
RVC	6-5/8	Inches	0	Feet	1130	Feet
ROTARY	3-7/8	Inches	1130	Feet	2535	Feet
		Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.2	4.25	.20	42	490
1.5	2.6	.140	490	1150

Perforations:
Type perforation SLOT
Size perforation .125"
From 1150 feet to 1950 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 52 FEET
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 364.2 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature COOL °F Quality FAIR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1773

Signed MARK WAITE *Mark Waite*
By driller performing actual drilling on site or contractor

Date 5-9-96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627