WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 52123
Permit No.
Basin 212

NOTICE OF INTENT NO. 17659

1. OWNER Triton Environmental Services
MAILING ADDRESS 476 E. So. Temple, #236 Salt Lake City, UT 84111
ADDRESS AT WELL LOCATION 1659 N. Main St. North Las Vegas, Nevada 89030

2. LOCATION SE ¼ SE ¼ Sec 22 T 20 N (S) R 61 E Clark County
PERMIT NO. MO-2598A (Issued by Water Resources) | 139-22-812-001 (Parcel No.) | Laurel Truck (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Monitoring Wells # 3 + 4				
Asphalt		0	.3	.3
Type II Fill		.3	1.0	.7
Brown Silty Sand		1.0	2.5	1.5
Dark Brown Sandy Clay		2.5	3.0	.5
Olive Silty Clay w/Sand		3.0	15.0	12.0
Caliche Layer		15.0	16.0	1.0
Olive silty gravel w/sand		16.0	21.0	5.0
Groundwater Encountered	16.5			
Reddish brown silty sand		21.0	23.0	2.0
Reddish brown Clay		23.0	26.0	3.0

MAY 28 1996

Date started 5-2, 1996
Date completed 5-2, 1996

7. WELL TEST DATA
TEST METHOD: [X] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	N/A	

8. WELL CONSTRUCTION
Depth Drilled 26 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)
6 Inches From 0 Feet To 26 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.70	schedule 40	0	25

Perforations:
Type perforation Slotted Screen
Size perforation 0.020
From 10 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 8
Placement Method: [ ] Pumped [X] Poured
Sand ~~Gravel~~ Packed: [X] Yes [ ] No
From 9 feet to 26 feet

Seal Type:
[ ] Neat Cement
[ ] Cement Grout
[X] Concrete Grout

9. WATER LEVEL
Static water level 16.5 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature Cool °F Quality poor

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name GES (Contractor)
Address 7560 W. Sahara St. 101 Las Vegas, Nevada 89117 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board Exempted (Engineer)
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1986
Signed [signature] By driller performing actual drilling on site or contractor
Date 5-23-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627