


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 52854  
 Rec. ....  
 Well No. ....  
 Permit No. ....  
*Do not fill in*



Owner Arthur & Neva Foster Driller Effinger Drilling & Pump Service

Address 314 Last Charleston Address P. O. Box 579 Lic. No. 212

Location of well: SE 1/4 SW 1/4 Sec. 26, T. 19N/S, R. 60E, in Clark County  
 or 6666 Ann Road

Water will be used for Domestic Total depth of well 250 feet

Size of drilled hole 12 inch Weight of casing per linear foot .134 12.15#

Thickness of casing .134 Temp. of water .....

Diameter and length of casing 8" ID 250 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 55 feet

If flowing well describe control works .....

Date of commencement of well September 11, 1965 Date of completion of well September 21, 1965

Type of well rig "Walker-Neer 31"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Clay & broken lime
10	12	2	Caliche
12	14	2	Limestone
14	20	6	Gravel
20	24	4	Gravel & Boulders
24	28	4	Caliche
28	40	12	Limestone
40	51	11	Caliche
51	64	13	White Limestone
64	68	4	Brown Limestone
68	72	4	Limestone (water)
72	91	19	Yellow Clay
91	93	2	Limestone (water)
93	103	10	Yellow Clay
103	105	2	Gravel (water)
105	125	20	Yellow Clay
125	140	15	White Clay
140	144	4	Yellow Clay
144	164	20	Red Clay
164	175	11	Limestone (water)
175	200	25	Red Clay
200	210	10	Limestone (water)
210	225	15	Red Clay
225	250	25	Limestone (water)

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 225 to 250 ft.

Other aquifers.....  
200-210  
164-175  
103-105  
91-93  
68-72

---

08  
 First water at.....feet.


---

Casing perforated  
 from 165 to 245 ft.

---

Size of perforations  
1/8" X 12" Torch

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
			

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" ID	0	250	250	Cemented from 0 to 50 feet 2½ yards of cement Graveled packed from 50 to 245 feet 5½ yards of pea gravel  Cap plate welded to top of casing.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Effinger Drill & Pump  
Well Driller

By A. Effinger

License No. 212

Dated September 22, 1965

(Not to be filled in by Driller)

**RECEIVED**

SEP 24 1965

DIV. OF WATER RESOURCES  
BRANCH OFFICE  
LAS VEGAS, NEVADA