

REVISED

WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA  
DIVISION OF WATER RESOURCES

OFFICE USE ONLY  
Log No. 52813  
Permit No. 212  
Basin. 212

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT  
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 15857  
Circle K Store #756

1. OWNER Circle K Stores Inc  
MAILING ADDRESS 3003 North Central Ave 16th Floor, Phoenix, AZ 85012  
2. LOCATION SW 1/4 Sec 13 T 21 N/S R. 60 E  
PERMIT NO. MO 2443 A, 100-443-005

3. WORK PERFORMED  
 New Well  Replace  Recondition  Deepen  Abandon  Other  
4. PROPOSED USE  
 Domestic  Municipal/Industrial  Irrigation  Test  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  Air  Other H2A

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Tan silty sandy clay		0	3	3
Tan silty sand		3	6.5	3.5
Brown Tan silt		6.5	11.0	4.5
Brown Tan clayey silt		11	30	19

8. WELL CONSTRUCTION  
Depth Drilled 30 Feet Depth Cased 30 Feet  
HOLE DIAMETER (BIT SIZE)  
From 11 Inches To 0 Feet 30 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"		1/4"	0	5
6"		1/4"	20	25

Perforations:  
Type perforation Factory slotted  
Size perforation  
From 0.040 5 feet to 20 feet  
From 0.020 25 feet to 30 feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  Cement Grout  Concrete Grout  
Depth of Seal 0'-3', 20'-24'  
Placement Method:  Pumped  Poured  
Gravel Packed:  Yes  No  
From 4 feet to 30 feet

9. WATER LEVEL  
Static water level: feet below land surface  
Artesian flow: G.P.M. P.S.I.  
Water temperature: °F Quality:


Date started 4/30/1996  
Date completed 4/30/1996

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name John M. Muley Contractor  
Address 3121 South Park Drive Tempe, AZ 85202  
Nevada contractor's license number issued by the State Contractor's Board 0041809  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1765T-M1  
Signed: By driller performing actual drilling on site or contractor  
Date:

OFFICE USE ONLY  
 Log No. 52873  
 Permit No. \_\_\_\_\_  
 Basin 212



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 15857  
Circle K Store #736

1. OWNER Circle K Stores, Inc ADDRESS AT WELL LOCATION Circle K Store #736  
2504 North Belmont  
Las Vegas, NV  
 MAILING ADDRESS 3003 N. Central Ave  
16th Floor Phoenix AZ 85012  
 2. LOCATION SW 1/4, SE 1/4 Sec. 13 T. 21 N/S R. 60 E County \_\_\_\_\_  
 PERMIT NO. MO 2443 A Parcel No. 100-443-006 Subdivision Name \_\_\_\_\_  
 Issued by Water Resources

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE:  
 Cable  Rotary  RVC  
 Air  Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Tan silty Sandy clay</u>		<u>0</u>	<u>3</u>	<u>3</u>
<u>Tan silty sand</u>		<u>3</u>	<u>6.5</u>	<u>3.5</u>
<u>Brown Tan silt</u>		<u>6.5</u>	<u>11.0</u>	<u>4.5</u>
<u>Brown Tan Clayey silt</u>		<u>11.0</u>	<u>30</u>	<u>19</u>

8. WELL CONSTRUCTION  
 Depth Drilled 30 Feet Depth Cased 30 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 11 Inches To 30 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6"</u>		<u>1/4"</u>	<u>0</u>	<u>30</u>

Perforations:  
 Type perforation Factory Slotted  
 Size perforation 0.20  
 From 10 feet to 30 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 0-16  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 10 feet to 30 feet

9. WATER LEVEL  
 Static water level \_\_\_\_\_ feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started 4-30 1996  
 Date completed 4-30 1996

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name John Manley Contractor  
 Address 3121 South Park Drive Contractor  
Tempe AZ 85282  
 Nevada contractor's license number issued by the State Contractor's Board: 0041809  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 1765T-M1  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date 5-20-96