


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. <b>530</b>	
Rec. _____	
Well No. _____	
Permit No. _____	
<i>Do not fill in</i>	

Owner Frank Bayman Drillers J. E. Howard

Address At Property Address 1634 Princeton St Lic. No. 139

Location of well: NE 1/4 1/4 Sec 25, T. 21 N/S, R. 61 E, in Clark County

or Lot 3 Block 2 Topaz Heights, 2 Blocks E of Topaz 2 Blocks So Bl  
Bond

Water will be used for Domestic Total depth of well 200

Size of drilled hole 12" & 8" Weight of casing per linear foot 7 1/2

Thickness of casing 12 Ga Temp. of water \_\_\_\_\_

Diameter and length of casing 8 5/8" 65'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 16'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.) 53

Date of commencement of well Nov 25 53 Date of completion of well Nov 30 53

Type of well rig Cable Tools

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	3	3	Hard Rock	
3	20	17	White Loche	Chief aquifer (water-bearing formation)
20	40	20	Red Clay	from <u>125</u> to <u>127</u> ft.
40	43	3	Sandy. Some Water.	Other aquifers <u>40-43</u>
43	93	93	Red Clay	
<del>93</del>				
130	175	45	Layers Red Clay & White Loche.	First water at <u>40</u> feet.
175	187	12	Red Clay & Gravel	Casing perforated
187	200	13	Water Raised To 16'	from _____ to _____ ft.
			Red Clay.	Size of perforations _____



