WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 53677
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Bill Mull — Driller: S.B.Rodgers and Coh

Address: Tonopah Highway — Address: 3200 Palomino lane — Lic. No. I56

Location of well: W ½ ¼ NE ¼ Sec I2, T. 20N/S, R. 60E, in CLARK County

or .....

Water will be used for domestic use — Total depth of well 100'

Size of drilled hole I2 I2 in — Weight of casing per linear foot I00

Thickness of casing I0 Gauge — Temp. of water .....

Diameter and length of casing 8"5/8 casing 100'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 4 46 ft

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well June 22 — Date of completion of well june26 59

Type of well rig Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	5	5	sand and gravel
5	I6	II	colechie
I6	60	49	white Clay
60	66	6	decomposed lime and gravel (WATER)
66	86	20	brown clay
86	90	4	broken rock gravel water
90	I00	I0	brown clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to 66 ft.

Other aquifers 85

First water at 60 feet.

Casing perforated
from 55 to 90 ft.

Size of perforations
¼ X 4 in

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8	00	I00		8 5/8 O D well casing to I00 ft. Perforated 55 to 90 gravel packet from I00 back to 50 ft cementet from 50 ft to surface I ½ yds RM

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed L B Rodgers
Well Driller

By.....

License No. 156

Dated June 25, 19 59

(Not to be filled in by Driller)