

State 702

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **53837**  
Rec. \_\_\_\_\_  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_



Owner Harry Cohen Driller Mc Kesson & Stock

Address 118 N. 3rd, ST., Las Vegas Nevada Room 1 Address 1629 N. Main, North Las Vegas, Nevada No. 200

Location of well: 1/4 Sec. 1/4, T. N/S, R. E, in Clark County

or T. 22S R. 61 E, sec. 33 N 1/2 SE 1/2 SE 1/2 SW 1/2, Mount Diablo Meridian

Water will be used for Domestic Total depth of well 200

Size of drilled hole 8 inch Weight of casing per linear foot 11.7

Thickness of casing 10 gauge Temp. of water Cool

Diameter and length of casing 8 inch 200 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 186

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 18 1955 Date of completion of well June 21 1955

Type of well rig Keystone # 50

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand and Gravel
2	163	161	Cemented Gravel
163	165	2	Clay and Gravel
165	186	86	Cemented Gravel
186	194	8	Gravel (water)
194	200	6	Cemented Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 186 to 194 ft.

Other aquifers \_\_\_\_\_

First water at 186 feet.

Casing perforated

from 160 to 200 ft.

Size of perforations

1/2 inch, 6 inches long  
staggered around casing



