

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 53842  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Chester L. & Ruth C. Ashby Driller Effinger Drilling & Pump Serv.  
 Address 1950 North Micheal Way Address 5488 West Duncan Dr. Lic. No. 212  
 Location of well: NE NW<sup>1/4</sup> SW<sup>1/4</sup> Sec. 24, T. 20N/S, R. 60E, in Clark County  
 or 1950 North Micheal Way  
 Water will be used for Domestic Total depth of well 200 ft.  
 Size of drilled hole 12 Inch Weight of casing per linear foot \_\_\_\_\_  
 Thickness of casing 7 Guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" ID 200 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well January 16, 1960 Date of completion of well January 24, 1960  
 Type of well rig "72 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sandy Clay & Gravel
3	5	2	Caliche
5	9	4	Yellow Clay
9	13	4	Limestone
13	16	3	Gravel
16	22	6	Limestone
22	27	5	Yellow Clay
27	31	4	Limestone
31	38	7	Red Clay & Gravel
38	41	3	Limestone
41	47	6	White Clay & Gravel
47	53	6	Limestone
53	61	8	Clay
61	69	8	Sand (Water)
69	78	9	Limestone
78	85	7	Gravel (Water)
85	90	5	Clay
90	104	14	Sand & Gravel
104	109	5	Limestone
109	117	8	Clay
117	128	11	Red Sandy Clay
128	200	72	Gravel (Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 128 to 200 ft.

Other aquifers 90-104  
78-85

First water at 61 feet.

Casing perforated 120 to 200 ft.

Size of perforations 1/8" X 15"



