


WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA



Log No. 54036
 Rec. 6/29 1955
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Walter C. & Helen M. Askew Driller S.R. Holladay & Son

Address 2214 Cedar Street, Las Vegas, Nev. Address 1042 South Main St., L.H. No. 45

Location of well: SE 1/4 SW 1/4 Sec. 36, T. 20 N/S, R. 60 E, in Clark County

or NE 1/4 of SE 1/4 of SE 1/4 of SW 1/4 of Section 36, Twp. 20S, Range 60

Water will be used for Domestic Total depth of well 175'

Size of drilled hole 12" to 50', 10" to 175' Weight of casing per linear foot 10 Gauge

Thickness of casing 10 Gauge Temp. of water _____

Diameter and length of casing 8" I.D. to 175'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 98'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 21 June 1955 Date of completion of well 24 June 1955

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	11	11	Caliche
11	27	16	Red sandy clay
27	30	3	Caliche
30	41	11	Red sandy clay
41	44	3	Caliche
44	76	32	Red sandy clay
76	79	3	Caliche
79	84	5	Red clay
84	87	3	Caliche
87	91	4	Red clay
91	94	3	Red sand water
94	117	23	Red clay
117	119	2	Caliche
119	124	5	Red sandy clay
124	127	3	Red sand water
127	130	3	Red clay
130	135	5	Red sand water
135	136	1	Gravel water
138	144	6	Red clay
144	148	4	Red sand water
148	169	21	Gravel water
165	175	10	Gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 165 to 175
~~154' to 160' ft~~

Other aquifers
135' to 136'
130' to 135'
126' to 127'
91' to 94'

91
 First water at _____ feet.

95 Casing perforated 175
 from _____ to _____ ft.

3/16" Size of perforations



