


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 54329  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not write*



Owner G. E. Toth Driller S. R. McKinney & Son

Address 2514 E. Owens ave, N. Las Vegas Address 1042 S. Main, Las Vegas No. 45

Location of well: NW 1/4 NW 1/4 Sec. 25, T. 20N/S, R. 61E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 125

Size of drilled hole 8" to 125 ft, 10" to 55 Weight of casing per linear foot 28 lb

Thickness of casing 5/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I. D. to 61' and 7"  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 20 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Sept 3, 1952 Date of completion of well Sept 5, 1952

Type of well rig  Bucyrus Erie 211, Sudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Surface soil	
3	60	57	White clay	
60	82	22	White clay	
82	84	2	Gyp rock	
84	101	17	White clay	Chief aquifer (water-bearing formation) from <u>118</u> to <u>125</u> ft.
101	103	2	Rock Water	Other aquifers <u>101 to 103</u>
103	118	15	White clay	
118	125	7	Brown sandy clay Water	
				First water at <u>20 ft.</u> feet.
				Casing perforated from _____ to _____ ft.
				Size of perforations _____

