


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 54368
 Rec.
 Well No.
 Permit No.



Owner R. E. Schroeder Driller S. R. McKinney & Son

Address 647 South Tonopah Drive, L.V. Address 1042 So. Main, L.V. Lic. No. 45

Location of well: SW¹/₄ SW¹/₄ Sec. 33 T. 20N/S, R. 61E, in Clark County

Water will be used for Domestic Total depth of well 175 ft.

Size of drilled hole 12" to 50', 10" to 175 Weight of casing per linear foot 10 Guage

Thickness of casing 10 Guage Temp. of water

Diameter and length of casing 8" I.D. to 175 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 15 ft.

If flowing well describe control works

Date of commencement of well April 22, 1955 Date of completion of well April 25, 1955

Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Clay
10	20	10	Caliche
20	30	10	White clay water
30	70	40	Clay water
70	125	55	White clay and water gravel
125	130	5	White clay and water
130	145	15	White clay
145	150	5	gravel water
150	168	18	Clay
168	175	7	Gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 168' to 175' ft.

Other aquifers 145' to 150'

125 to 130'

30' to 70'

20' to 30'

First water at 30 feet.

Casing perforated

from 115 to 175 ft.

Size of perforations

3/16" x 10"



