

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 54506  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Don Leytham Driller Patrick H. Thompson

Address 2419 Gateway Drive Address 217 so. 26th St Lic. No. 192

Location of well: SW 1/4 Sec. 18, T. 20N/S, R. 62E, in Clark County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 150 ft.

Size of drilled hole 0 to 50' - 12" 50 to 150' Weight of casing per linear foot 12 lb.

Thickness of casing 10 gauge Temp. of water cool

Diameter and length of casing 8 5/8" in diameter 151 ft. in length  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 27 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Feb. 9, 1962 Date of completion of well Feb. 12, 1962

Type of well rig Cable tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	34	34	Brown clay
34	40	6	Gravel
40	50	10	Brown clay and gravel
50	60	10	Brown sandy clay
60	75	15	White clay
75	90	15	Brown clay
90	105	15	White clay
105	120	15	Grey clay
120	122	2	Gravel
122	135	13	Grey clay
135	137	2	Gravel
137	150	13	Grey clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 90 to 105 ft.

Other aquifers 50 - 55,  
60 - 75, 120 - 122  
135 - 137,

---

First water at 50 feet.

Casing perforated

from 55 to 150 ft.

Size of perforations

3/16 X 12" 4 rows

