

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

DEEPENING JOB

Log No. 54502  
 Rec. [Stamp]  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner Rodney Colton Driller S.R. McKinney & Sons, Inc.

Address P.O. Box 3144, North Las Vegas Address 1042 So. Main Lic. No. 45

Location of well: NW 1/4 SE 1/4 Sec. 19, T.20 N/S, R.6 E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 175'

Size of drilled hole 8" to 175' Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 6" ID from 0' to 120' to 175'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 38'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 6/19/62 Date of completion of well 6/21/62

Type of well rig Bucyrus Erie 24L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
125	148	23	grey sandy clay
148	155	7	brown gravelly clay(water)
155	175	20	brown sandy clay(water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 155 to 175' ft.

Other aquifers 148 to 155'

First water at \_\_\_\_\_ feet.

Casing perforated

from 120 to 175 ft.

Size of perforations

3/16" X 10"



