

State

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55204  
Rec. 19  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Press Lamb Driller S.R. McKinney & Sons, Inc.

Address 4725 East College Address 1042 So. Main Lic. No. 45

Location of well: NE 1/4 SE 1/4 Sec. 19, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 200 feet

Size of drilled hole 12" to 50 ft., 10" to 200 ft. Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8 5/8" OD from 0 ft. to 202 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface 54 feet

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 6/17/61 Date of completion of well 6/24/61

Type of well rig Pucyrus Eric 24 L

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	soil & clay
2	30	28	clay
30	70	40	sandy clay
70	75	5	clay
75	80	5	sandy clay (little water)
80	95	15	clay
95	105	10	sandy clay (water)
105	136	31	sandy clay
136	149	13	gravel (water)
149	155	6	gravel / gravelly clay
155	160	5	sandy clay (water)
160	175	15	clay
175	200	25	lite clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
from 155 to 160 ft.

Other aquifers 136 to 149 '  
75 to 80 '  
95 to 105 '

First water at 75 feet.

Casing perforated  
from 100 to 200 ft.

Size of perforations  
3/16" x 10"



