WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55297
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner W. F. Moon Driller [illegible] Mitchell

Address ..... Address 310 E. College Lic. No. 63

Location of well: SE ¼ NE ¼ Sec. 19, T. 20 N/S, R. 62 E, in Clark County

or East College Rd.

Water will be used for Domestic Total depth of well 100

Size of drilled hole 8" Weight of casing per linear foot 16

Thickness of casing 14 gauge Temp. of water .....

Diameter and length of casing 50 ft 8" casing

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure non flowing

If nonflowing well give depth of standing water from surface 39 ft

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well July 13 1954 Date of completion of well July 14 1954

Type of well rig .....

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Clay
5	20	15	Hard pan
20	25	5	Clay
25	30	5	Hard pan
30	35	5	Clay
35	40	5	Hard pan
40	47	7	gravel - water
47	50	3	clay (Red)
50	60	10	Clay (Red)
60	65	5	gravel - water
65	75	10	Clay
75	80	5	Hard pan
80	85	5	gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 60 to 65 ft.

Other aquifers 80-85 - 95-100 - gravel

First water at 40 feet.

Casing perforated

from none to ..... ft.

Size of perforations

none

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
85	95	10	Clay
95	100	5	Clay & gravel

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	50	50	50 ft of 8" Casing 1 yd of Sand & Cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Hairgrove Drilling Co.
Well Driller

By.....

License No. 63

Dated 7/15, 1954

(Not to be filled in by Driller)