


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55309
 Rec. 19
 Well No. 133
 Permit No. 133

Do not fill in



Owner K. B. Whittaker Driller Nevada Pump & Supply Co.
1400 E. Lewis
 Address c/o Dale Cook, Las Vegas, Nev. Address 412 S. 4th, Las Vegas, Nev. No. 133

Location of well: NE 1/4 SE 1/4 Sec 1, T21 N/S, R60 E, in Clark County
 or.....

Water will be used for Domestic Total depth of well 150'

Size of drilled hole 12" Weight of casing per linear foot 11.6

Thickness of casing 10 ga. Temp. of water.....

Diameter and length of casing 8" x 150'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 68'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well January 16, 1955 Date of completion of well January 18, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	12	9	Caliche
12	60	48	Sandy Clay
60	68	8	Sandstone
68	70	2	Very fine sand-very little water
70	85	15	Sandy clay
85	100	15	Sandstone
100	112	12	gravel & sand-water bearing
112	130	18	Sandy clay
130	136	6	Large gravel - water
136	145	9	Sandy clay
145	148	3	Gravel - water bearing
148	150	2	Sandstone

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 130 to 136 ft.

Other aquifers.....

145 - 148

100 - 112

68 - 70

First water at 68 feet.

Casing perforated

from 100 to 150 ft.

Size of perforations

1/16 x 6"



