


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55357
 Rec.
 Well No.
 Permit No.
Do not fill in



Owner Don Orvel Barnes Driller S. R. McKinney & Son

Address 1577 Redondo Avenue, Salt Lake City Address 1042 South Main, L.V. Lic. No. 45

Location of well: SE 1/4 SW 1/4 Sec 11, T. 21 N/S, R. 60 E, in Clark County County
 or E 1/2 of SE 1/4 of SE 1/4 of SW 1/4 Sec. 11 Twp 21, R 60 E.

Water will be used for Domestic Total depth of well 208 1/2 ft.

Size of drilled hole 12" to 50' 10" to 185' Weight of casing per linear foot 10 Gauge
8" to 208

Thickness of casing 10 Gauge Temp. of water

Diameter and length of casing 8" I.D. to 208'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 140'

If flowing well describe control works

Date of commencement of well April 8, 1955 Date of completion of well April 12, 1955

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	35	35	Cemented Gravel
35	55	20	Caliche
55	65	10	Clay
65	95	30	Caliche
95	120	25	Clay
120	140	20	Sand & Silt
140	165	25	Clay
165	180	15	Cemented Gravel
180	190	10	Sand & Water
190	200	10	White Sand & Water
200	208	8	Sandy Gravel & Water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 200 to 208 ft.

Other aquifers 180 to 200

First water at 180 feet.

Casing perforated from 168 to 208 ft.

Size of perforations 3/16" by 10"



