


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55365  
 Rec. 19  
 Well No.   
 Permit No.   
*Do not fill in*

Owner Robert D. Dickirson Galli? Driller S. R. McKinney & Son  
 Address 1042 South Main St. Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: S<sup>1</sup>/<sub>4</sub> SE<sup>1</sup>/<sub>4</sub> Sec. 11, T. 21N/S, R. 60E, in Clark County  
 or East 1/2 of SE 1/2 of SW 1/2 of SE 1/2 of Section 11, Twp. 21, Range 60 E.  
 Water will be used for Domestic Total depth of well 205 ft.  
 Size of drilled hole 12" to 50 ft., 10" to 205 Weight of casing per linear foot 10 guage  
 Thickness of casing 10 guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 205 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 135 ft.  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well Feb. 17, 1955 Date of completion of well Feb. 24, 1955  
 Type of well rig 72 Speed Star Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	surface sand
2	15	13	caliche
15	18	3	clay
18	29	11	caliche
29	35	6	soft caliche
35	54	19	caliche
54	60	6	soft caliche
60	90	30	caliche
90	110	20	clay
110	165	55	sandy clay
165	205	40	sand and gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 165 to 205 ft.

Other aquifers \_\_\_\_\_

First water at 165 feet.

Casing perforated  
 from 165 to 205 ft.

Size of perforations  
3/16" X 10"



