

**WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA Revised**

Log No. 55387
 Rec. 6/3 1955
 Well No.
 Permit No.
Do not fill in



Owner William Maxwell Driller Nevada pump & Supply Company
 Address 1012 Sahara Way, Las Vegas, Nev. Address 412 S. 4th, Las Vegas, Nev. Lic. No. 133
 Location of well: NE 1/4 NW 1/4 Sec. 11., T. 21 N/S, R. 60 E, in Clark County

Water will be used for Domestic Total depth of well 222 feet

Size of drilled hole 12" Weight of casing per linear foot 12 lb

Thickness of casing 10 ga. Temp. of water

Diameter and length of casing 8" x 60' & 6" x 176' liner
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 185 feet

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well March 9, 1955 Date of completion of well March 12, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Top Soil
4	16	12	Caliche
16	69	53	Cemented Gravel
69	77	8	Hard Rock Ledge
77	90	13	Cemented Gravel
90	99	9	Hard Rock Ledge
99	191	92	Cemented Gravel
191	198	7	Sand-Water Bearing
198	212	14	Hard Rock
212	222	10	Sand-Gravel-Water Bearing

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 212 to 222 ft.

Other aquifers 191 - 198

First water at 191 feet.

Casing perforated
 from 162 to 222 ft.

Size of perforations
1/16" x 6"

