

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55390  
 Rec. ....19  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner Raymond W. Morich Driller Patrick H. Thompson  
 Address 1530 Chapman Drive, Las Vegas, Nevada Address 217 So. 26th St. LV. Nev. Lic. No. 192  
 Location of well: SE 1/4 SE 1/4 Sec. 11, T21-N/S, R60 E, in Clark County  
 or E 1/2 SW 1/4 SE 1/4 of above section  
 Water will be used for Domestic Total depth of well 195'  
 Size of drilled hole 12" to 50' -- 10" to 175' Weight of casing per linear foot 8" -- 12.2 -- 6" -- 9.32  
 Thickness of casing 10 ga. Temp. of water .....  
 Diameter and length of casing 8" -- 176' 6" -- 27'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure .....  
 If nonflowing well give depth of standing water from surface 150'  
 If flowing well describe control works .....  
 (Type and size of valve, etc.)  
 Date of commencement of well May 3, 1955 Date of completion of well May 6, 1955  
 Type of well rig Star 71 Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	83	83	cemented gravel
83	120	37	sandy brown clay
120	125	5	cemented gravel
125	173	48	sandy brown clay
173	195	22	cemented gravel--water bearing

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 173 to 195 ft.

Other aquifers.....  
none

---

First water at 173 feet.

Casing perforated  
 from 160 to 195 ft.

Size of perforations  
3/16x12--4 rows

