

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55412
 Res. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Clark Sloniger Driller Nevada Pump & Supply Company

Address 2187 Walnut Rd., N. Las Vegas, Nev. Address Las Vegas, Nevada Lic. No. 133

Location of well NE 1/4 NW 1/4 Sec. 19, T.20 N/S, R.62 E, in Clark County

or 2187 Walnut Rd., Las Vegas, Nevada

Water will be used for Domestic Total depth of well 102 feet

Size of drilled hole 10" Weight of casing per linear foot 9 lbs.

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 6" x 102'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 31 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well May 7, 1955 Date of completion of well May 7, 1955

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	9	6	Sandy Clay
9	13	4	Clay
13	27	14	Soft Limestone
27	41	14	Sandy Clay
41	55	14	Sand-Water Bearing
55	57	2	Limestone
57	63	6	Gravel-Water Bearing
63	74	11	Sticky Clay
74	77	3	Hard Limestone
77	91	14	Sand-Gravel-Water Bearing
91	102	11	Sticky Tough Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 77 to 91 ft.

Other aquifers 41 - 55

57 - 63

First water at 41 feet.

Casing perforated

from 52 to 102 ft.

Size of perforations

1/16" x 6"

10/19
DIS

