

57

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55468
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in



Owner Stewart Turnbaugh Driller S. R. McInnes & Sons, Inc.

Address 2438 Bassler, North Las Vegas Address 1042 South Main Lic. No. 45

Location of well: NE 1/4 NW 1/4 Sec. 19, T20 N/S, R62 E, in Clark County

or _____

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 12" to 50', 10" to 200' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" ID from 0' to 200'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 68'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 2/7/62 Date of completion of well 2/12/62

Type of well rig Rucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	top soil
8	20	12	gravelly clay
20	60	40	grey clay
60	61	1	gravel
61	75	14	grey clay
75	110	35	grey gritty clay(water)
110	130	20	sandy clay
130	155	25	grey gritty clay(water)
155	174	19	brown sandy clay
174	180	6	brown clay
180	185	5	grey sandy clay
185	200	15	brown sandy clay(water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 185 to 200 ft.

Other aquifers 75 to 110
130 to 155

First water at 75 feet.

Casing perforated
 from 80 to 100 ft.
120 to 200'

Size of perforations
3/16" x 10"

