

Water type office

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55483
 Rec. 7/16 1955
 Well No. _____
 Permit No. _____
Do not fill in

Owner John W. Larson Driller S.R. McKinney & Son
 Address 1477 Redondo Ave. Salt Lake City, Utah Address 1042 So. Main. L. V. Lic. No. 45
 Location of well: SW $\frac{1}{4}$ SW $\frac{1}{4}$ Sec. 12, T. 21N/S, R. 60E, in Clark County
 or E $\frac{1}{2}$ of NE $\frac{1}{4}$ of SW $\frac{1}{4}$ of SW $\frac{1}{4}$ of Sec 12, Range 21, Twp. 21, Range 60
 Water will be used for Domestic Total depth of well 185'
 Size of drilled hole 12" to 50, 10" to 185' Weight of casing per linear foot 10 Gauge
 Thickness of casing 10 guage Temp. of water _____
 Diameter and length of casing 8" I.D. to 185'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 100'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well 14 July 1955 Date of completion of well 16 July 1955
 Type of well rig Bucyrus Erie, 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	4	4	Caliche
4	25	21	Sand stone
25	55	30	Cement gravle
55	65	10	Sandy clay
65	72	7	Cement gravel
72	115	43	Sandy clay
115	122	7	Sand & gravel water
122	162	40	Sandy clay
162	174	12	Sand water
174	180	6	Clay & sand
180	185	5	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 162 to 174 ft.
 Other aquifers 115 - 122

First water at 115 feet.

Casing perforated
 from 145 to 185 ft.

Size of perforations
3/16" x 10"

