WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55507
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: C. J. ADDINGTON Driller: Joseph E. Metz

Address: ..... Address: Las Vegas Lic. No. 35

Location of well: SW.SW.NW ¼ ¼ ¼ Sec. 20, T. 20 N/S, R. 62 E, in Clark County

or .....

Water will be used for: Domestic Total depth of well: 75

Size of drilled hole: 10" Weight of casing per linear foot: 16#

Thickness of casing: 5/32 Temp. of water: 68

Diameter and length of casing: 8" OD x 49'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 33'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: Feb 21-53 Date of completion of well: March 4-1953

Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	silt
8	11	3	hardpan
11	30	19	gravel in clay
30	39	9	gravel w 28
39	42	3	clay
42	47	5	gravel w 10 8
47	62	15	gravel in clay
62	67	5	broken lime w 25 8
67	75	8	clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 62 to 67 ft.

Other aquifers 42 - 47

First water at 35 feet.

Casing perforated
from 40 to 49 ft.

Size of perforations
1/8 x 6" every 2'

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" O.D.	1' above	48'	49'	gravel pack 35'-48' Top 35' cemented

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailer 25 g.P.M. to 38'

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Joseph E. Metz
Well Driller

By J. E. M.

License No. 35

Dated March 21, 1953

(Not to be filled in by Driller)