

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55510

Rec. \_\_\_\_\_ 19\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

*Do not fill in*

Owner Richard Alexander Driller S. R. McKinney & Son

Address 1656 Betty Lane, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 SW 1/4 Sec. 20, T20 N/S, R62 E, in Clark County \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 50 ft, 10" to 100 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 100 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 34 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Feb. 6, 1966 Date of completion of well Feb. 7, 1956

Type of well rig 72 Speed Star Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	45	45	brown clay
45	65	20	brown gravelly clay water
65	75	10	white clay
75	80	5	brown sandy clay
80	85	5	brown sandy clay water
85	100	15	brown sand and clay water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 85 to 100 ft.

Other aquifers 80 to 85  
45 to 65

---

First water at 45 feet.

---

Casing perforated

from 60 to 100 ft.

---

Size of perforations

3/16" X 10"

