

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55550  
 Rec. 6/29 1955  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

**Myron Rohde**  
 Owner..... Driller **S.R. McKinney & Son**  
 Address..... Address **1042 So. Main, L.V.** Lic. No. **45**  
 Location of well: **NW 1/4 SW 1/4 Sec. 12, T. 21N/S, R. 60E, in Clark** County  
 or **W 1/2 of SW 1/4 of NW 1/4 of SW 1/4 of Section 12, Twp. 21, Range 60**  
 Water will be used for **Domestic** Total depth of well **190'**  
 Size of drilled hole **12" to 50, 10" to 190'** Weight of casing per linear foot **10 Gauge**  
 Thickness of casing **10 Gauge** Temp. of water.....  
 Diameter and length of casing **8" I.D. to 190'**  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface **130'**  
 If flowing well describe control works.....  
 (Type and size of valve, etc.)  
 Date of commencement of well **25 June 1955** Date of completion of well **28 June 1955**  
 Type of well rig **Bucyrus Erie 24L, Spudder**

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	48	48	Cement gravel
48	70	22	Clay & gravel
70	95	25	Sandy clay
95	105	10	Sand
105	110	5	Sandy clay
110	115	5	Cement gravel
115	120	5	Cement gravel
120	140	20	Sandy clay
140	155	15	Sand & Clay
155	165	10	Sand water
165	180	15	Sand water
180	190	10	Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from **165** to **180** ft.  
**155' to 165'**

Other aquifers.....

---

First water at **155** feet.

---

Casing perforated  
 from **150** to **190** ft.

---

Size of perforations  
**3/16" x 10"**

