


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55637
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in



Owner Ray Harris Driller S. R. McKinney & Sons, Inc.

Address 2787 Edmons St., L.V. Address 1012 South Main Lic. No. 45

Location of well: N 1/4 NW 1/4 Sec. 12, T. 21 N/S, R. 6 E, in Clark County
 or _____

Water will be used for Domestic Total depth of well 300'

Size of drilled hole 12" to 50', 10" to 300' Weight of casing per linear foot 10 gauge

Thickness of casing 10 gauge Temp. of water _____

Diameter and length of casing 8" ID from 0' to 300'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 125'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Oct. 2, 1963 Date of completion of well Oct. 21, 1963

Type of well rig Bucyrus Erie 22W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sandy clay
30	55	20	Clay & gravel
55	70	15	gravel
70	75	5	sandy clay
75	125	50	sandy clay & gravel
125	130	5	gravel (water)
130	160	30	gravelly clay
160	180	10	sandy clay
170	200	30	sandy clay (water)
200	300	100	clay cement gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 200 to 300 ft.

Other aquifers 125 to 130'

170 to 200'

First water at 125' feet.

Casing perforated

from 215 to 295' ft.

Size of perforations

3/16" X 10"



