WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55732
Rec. 19
Well No.
Permit No.
Do not fill in

Owner: James Q. Thiriot — Driller: Patrick H. Thompson

Address: Flamingo Road, Las Vegas, Nev. — Address: 217 So 26th St LV. Nev. Lic. No. 192

Location of well: SE¼ SW¼ Sec. 13, T. 21 N/S, R. 61 E, in Clark County

or

Water will be used for: Domestic — Total depth of well: 173'

Size of drilled hole: 12" to 50' - 10" from 50' to 173' — Weight of casing per linear foot: 28#

Thickness of casing: ¼" — Temp. of water: Cold

Diameter and length of casing: 8" dia. - 174' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 10'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Dec. 1, 1955 — Date of completion of well: Dec. 4, 1955

Type of well rig: Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Surface soil
5	30	25	White clay
30	34	4	Gravel
34	60	26	White clay
60	65	5	Gravel
65	140	75	Red sandy clay - streaks of gravel
140	165	25	Red clay
165	173	8	Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 165 to 173 ft.

Other aquifers: 30 - 34

First water at 34 feet.

Casing perforated

from 125 to 173 ft.

Size of perforations

3/16 x 12 - 4 rows

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	+1	173	174	Cemented to 57'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 25 G. P. M. from 35'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Patrick H. Thompson
Well Driller

By.....

License No. 192

Dated Dec. 7, 1955

(Not to be filled in by Driller)