


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 55779  
 Rec. 8/7/5 1955  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner J. J. [unclear] Driller Louis F. Evans  
 Address 664 Ave. 21 Boulder City Nevada Address 2020 Carroll N. Las Vegas Lic. No. 117  
 Location of well: S.W. 1/4 S. E 1/4 Sec. 14, T. 21N/S, R. 61E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 160 ft.  
 Size of drilled hole 50 ft. 12 inch. 110 ft. 10 inch Weight of casing per linear foot 11 lbs.  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8 inch O.D. pipe 160 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 29 ft. 1 inch.  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well June 22, 1955 Date of completion of well June 24, 1955  
 Type of well rig Keystone

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	23	23	yellow clay
23	29	6	red sandy clay
29	44	15	red sticky clay
44	46	2	red sand (water)
46	49	3	sand rock
49	53	4	yellow sandy clay
53	58	5	lime rock
58	64	6	gravel (water)
64	78	14	yellow clay
78	86	8	gravel
86	95	9	red sandy clay
95	107	12	lime rock
107	118	11	red sandy clay
118	126	8	lime rock
126	135	9	red sticky clay
135	141	6	gravel (water)
141	150	9	red sandy clay
150	160	10	lime rock & gravel

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 135 to 141 ft.

Other aquifers 58 to 64

---

First water at 44 feet.

Casing perforated  
 from 60 to 160 ft.

Size of perforations  
1/2 inch wide 6 inches long

