WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55839
Rec. ..... 19.....
Well No. 1
Permit No. .....
Do not fill in

Owner Fredrick T. Silk Driller S. R. McKinney & Son

Address 623 West Tichenor St. Compton 3, Cal. Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: ¼ NW ¼ Sec. 20, T. 20 N/S, R. 62 E, in Clark County

or .....

Water will be used for Domestic Total depth of well 150

Size of drilled hole 12" to 60 ft, 8" to 150 Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water .....

Diameter and length of casing 8" I.D. to 103 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 32 ft.

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well Feb. 5, 1953 Date of completion of well Feb. 16, 1953

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Light brown clay
40	135	95	Brown clay Sandy Water at 40
135	150	15	Yellow sandy clay Water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 135 to 150 ft.

Other aquifers .....

First water at 40 ft. feet.

Casing perforated

from 60 to 103 ft.

Size of perforations

¼" slots

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D.	0	103	103	8" cemented down to 60 ft. with 1 1/2"yds concrete

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 80 G.P.M. lowered water level to 30 ft.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed M. McKinney
Well Driller

By.....

License No. 45

Dated 3-9, 19 53

(Not to be filled in by Driller)