

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55888  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner M. J. Beckett & Meikle Driller S. R. McKinney & Son

Address Box 1871, Las Vegas Nev. Address 1042 S. Main Lic. No. 45

Location of well: NE 1/4 SW 1/4 Sec 21, T20 N/S, R62 E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft., 8" to 100 ft. Weight of casing per linear foot 18 lb.

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 60 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 40 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 12, 1953 Date of completion of well May 13, 1953

Type of well rig Bucyrus Erie 24 L, Soudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	red sandy clay
15	30	15	red clay
30	40	10	gravel dry
40	55	15	gravel water
55	65	15	red sandy clay
65	70	5	red sandy water
70	75	5	red sandy clay
75	80	5	red sand water
80	90	10	white sandy clay
90	95	5	white sand water
95	100	5	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 90 to 95 ft.

Other aquifers 75 to 80

65 to 70, 40 to 55

First water at 40 feet.

Casing perforated

None

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations



