3rd option Well

Log No. 55908
Rec. June 27 1955
Well No.
Permit No.
Do not fill in this space

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Las Vegas Children's Campes

Owner Thomas Lester Jones — Driller Douglas Slack

Address P.O. Box 1043 Las Vegas — Address P.O. Box 2081 LV — Lic. No. 137

Location of well: N½ NE¼ SE¼ NE¼ ¼ ¼ Sec. 23, T. 21 N/S, R. 61 E, in Clark County

or Flamingo Rd & Mesquite

Water will be used for Domestic — Total depth of well 225

Size of drilled hole 8 in — Weight of casing per linear foot 11.9 lbs

Thickness of casing 10 gage — Temp. of water Cool

Diameter and length of casing 220 ft of 10 gage - top 5 ft is ¼" Standard 8"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 9 ft.

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 2 1955 — Date of completion of well May 12 1955

Type of well rig Keystone 50 (53)

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand
2	16	14	Gravel
16	32	16	Lime Rock
* 32	36	4	Red Sand & Water
36	42	6	Yellow Clay
42	53	11	Red Sticky Clay
53	57	4	Lime Rock
57	62	5	yellow Clay
62	67	5	Lime Rock
67	71	4	Red Sticky Clay
71	84	13	Lime Rock
84	96	12	Yellow Sticky Clay
96	109	13	Lime Rock
109	121	12	Red Stick Clay
121	128	7	Lime Rock

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 217 to 225 ft.

Other aquifers 32 ft to 36 ft

First water at 32 feet.

Casing perforated
from 55 to 225 ft.

Size of perforations
3/16 in x 6 in

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material
128	139	11	Red Sandy Clay
139	155	16	Red Sticky Clay
155	163	8	Lime Rock
163	177	14	Red Sand clay
177	183	6	Lime Rock
183	190	7	Red Stick Clay
190	213	23	Lime Rock
213	217	4	Red Sand clay
*217	225	8	Lime Rock + Water

JUN 27 55 RECEIVED

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 × 1/4	0	5	5	8" Standard 1/4 in pipe
~~8~~	~~225~~			
8"	5	225	220	8" 10 gage pipe grouted in from 0 ft to 51 ft - gravel packed from 51 ft to 225 ft

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Well will del approx 2000 GPH, draw down is 20 ft expected to have slight flow in Winter Time

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Douglas Slagle
Well Driller

By Self

License No. 137

Dated June 10, 1955

Dell Effinger was driller on job

(Not to be filled in by Driller)