


Stack
Y

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. **55947**
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in



Owner Eddie Gilbreath Driller S.R. McKinney & Sons, Inc.

Address 4418 W. Charleston Address 1042 So. Main Lic. No. 45

Location of well: SE 1/4 NW 1/4 Sec. 25, T. 21N/S, R. 61E, in Clark County

Water will be used for Domestic Total depth of well 200 feet

Size of drilled hole 10", reamed 12" to 50 feet Weight of casing per linear foot 10 ga.

Thickness of casing 10 ga. Temp. of water _____

Diameter and length of casing 8" x 200 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 30 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 6/29/60 Date of completion of well 7/2/60

Type of well rig Bucyrus Erie 24L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Caliche
8	60	52	red clay & gravel streaks
60	93	33	brown clay & gravel streaks
93	110	17	brown clay & gravel streaks
110	114	4	gravel
114	135	21	brown clay & gravel
135	148	13	brown clay & gravel streaks
148	152	4	gravel with clay streaks
152	162	10	brown gravelly clay
162	170	8	brown gravelly clay
170	174	4	gravel
174	192	18	clay and gravel
192	202	10	cemented gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 174 to 202 ft.

Other aquifers 110-135
148-162

First water at 45 feet.

Casing perforated
 from 140 to 200 ft.

Size of perforations
3/16" x 10"



