

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55973  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Bonnie Joe Inc. I House Driller S. R. McKinley & Son  
 Address Box 1871, Las Vegas Nevada Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: NE 1/4 NW 1/4 Sec. 21, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft., 8" to 100 ft Weight of casing per linear foot 22 lb.

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 40 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 38 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well March 23, 1953 Date of completion of well March 24, 1953

Type of well rig Bucyrus Erie 241 Spudder

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	3	3	Top soil	
3	28	25	Brn <del>xxx</del> sandy clay	Chief aquifer (water-bearing formation)
28	52	24	soft sandy clay	from <u>76</u> to <u>100</u> ft.
52	66	14	brn sandy clay, Water	Other aquifers <u>52 to 66</u>
66	76	10	soft sandy clay	
76	88	12	soft white sandy clay Water	
88	100	12	brn sandy clay Water	First water at <u>52</u> feet.
				Casing perforated
				from _____ to _____ ft.
				Size of perforations



