

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55975

Rec. \_\_\_\_\_ 19\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

Do not fill in

Owner Bonnie Joe Inc. K. house Driller D. R. McKinney & Son

Address Box 1871, Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NE 1/4 NW 1/4 Sec. 21, T. 20 N/S, R. 62 E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft., 8" to 100 ft. Weight of casing per linear foot 22 lb.

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 60 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 38 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well March 25, 1953 Date of completion of well March 25, 1953

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Brn. sandy clay
18	29	11	hard brn clay
29	33	4	gravel
33	42	9	gravelly sand
42	48	6	Gravel
48	79	31	white sandy clay water
79	100	21	brn sandy clay Water

Water-bearing Formation, Casing Perforations, Etc.

**Chief aquifer (water-bearing formation)**

from 79 to 100 ft.

Other aquifers 48 to 79

First water at 48 feet.

Casing perforated

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations



