

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55992  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner M. J. Lakan Driller Patrick H. Thompson

Address 5250 Irvine St. Address 217 So. 26th St. Lic. No. 122

Location of well: S1/4 NE 1/4 Sec. 25, T21N/S, R6/E, in \_\_\_\_\_ County  
or \_\_\_\_\_

Water will be used for domestic Total depth of well 200 ft.

Size of drilled hole 12" to 50ft. 10" to 200ft weight of casing per linear foot 17#

Thickness of casing 3/16" Temp. of water cold

Diameter and length of casing 3 5/8 in. dia. 201 ft. length  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 27 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Aug. 9, 1961 Date of completion of well Aug. 14, 1961

Type of well rig cable tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	white clay and gravel
15	55	40	brown clay
55	59	4	brown clay and gravel- H2O
59	95	36	brown clay
95	185	90	brown clay with streaks of gravel carrying water
185	200	15	brown sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 95 to 185 ft.

Other aquifers 55 to 59

First water at 55 feet.

Casing perforated

from 50 to 200 ft.

Size of perforations

3/16x 12" 4 rows

