

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

56057

Log No. _____

Rec. _____

Well No. _____

Permit No. _____

Do not fill in



Owner Ruth Berg Driller Patrick H. Thompaon

Address Las Vegas, Nevada Address 217 S. 26th St. L.V.N. Lic. No. 192

Location of well: SW 1/4 NE 1/4 Sec 26, T21 N/S, R. 61 E, in Clark County

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 12" to 50' - 10" from 50' to 200' Weight of casing per linear foot 17#

Thickness of casing 3/16" Temp. of water Cool

Diameter and length of casing 8 5/8" dia. 201' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 15'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well Sept. 1, 1961 Date of completion of well Sept. 5, 1961

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	10	10	Sandy clay	
10	15	5	Hard sand	
15	25	10	Red clay	
25	35	10	red clay with stks white clay	Chief aquifer (water-bearing formation) from 150 to 165 ft.
35	55	20	light brown clay	
55	75	20	white sticky clay	Other aquifers 82 - 84
75	82	7	red clay	
82	84	2	clay & gravel - water	
84	95	11	red clay	
95	105	10	red clay with stks white clay	
105	115	10	red clay	
115	135	20	red clay with stks white clay	
135	140	5	white clay	
140	150	10	sandy red clay	First water at 30 feet.
150	165	15	sandy clay & gravel - water	
165	197	32	sandy red clay	
197	200	3	red clay	Casing perforated from 80' to 200 ft.
				Size of perforations 3/16 x 12 - 4 rows



