

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56058  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner T. A. Blasius Driller S. R. McKinney & Son  
 Address 2133 W. Bonanza Road, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: SE 1/4 NW 1/4 Sec. 26, T. 21N/S, R. 61E, in Clark County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 205 ft.

Size of drilled hole 12" to 80 ft, 8" to 205 Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 87 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface Surface

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well March 31, 1953 Date of completion of well April 2, 1953

Type of well rig Cucyrus Erie 21 L. Snudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Sandy clay	
3	10	7	Caliche	
10	20	10	white clay	
20	30	10	red sandy clay	
30	40	10	red sand and gravel	Water
40	55	15	red sandy clay	
55	62	7	caliche	Water
62	95	33	red sandy clay	
95	100	5	limestone	
100	110	10	red sand	Water
110	130	20	red sandy clay	
130	135	5	red sandstone	Water
135	160	25	red sandy clay	
160	165	5	red sand and gravel	Water
165	185	20	red sandy clay	
185	205	20	red sand with streaks of sandstone,	Water

**Chief aquifer (water-bearing formation)**  
 from 185 to 205 ft.  
 Other aquifers 160 to 165  
130 to 135  
100 to 110

First water at 30 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

