

State

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 516063
 Rec. [Stamp]
 Well No. _____
 Permit No. _____
 Do not write

Owner W.L. Burns Driller S.R. McKinney & Sons, Inc.

Address 12340 1/2 Victory Blvd. N. Hollywood California Address 1042 So. Main Lic. No. 45

Location of well: SE 1/4 SW 1/4 Sec. 26, T21 N/S, R. 01 E, in Clark County

Water will be used for Domestic Total depth of well 180 ft.

Size of drilled hole 10" reamed 12" to 50 ft. Weight of casing per linear foot 10 Ga.

Thickness of casing 10 Ga. Temp. of water _____

Diameter and length of casing 8-5/8" O.D by 180 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 16 feet

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 10/10/60 Date of completion of well 10/17/60

Type of well rig Bucyrus Erie 24L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Top Soil
2	8	6	Caliche
8	40	32	Red Sandy Clay
40	42	2	Gravel-water
42	60	18	Brown Sandy Clay
60	80	20	Light Brown Sandy Clay
80	95	5	Light Brown Sandy Clay
95	100	5	Red Sandy Clay
100	102	2	Gravel-water
102	130	28	Brown Sandy Clay
130	133	3	Gravel-water
133	147	14	Brown Sandy Clay
147	150	3	Gravel
150	166	16	Brown Sandy Clay
166	172	6	Gravel-water
172	180	8	Brown Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 166 to 172 ft.

Other aquifers 40-42, 100-102
130-133, 147, 150

First water at 40 feet.

Casing perforated
 from 80 to 176 ft.

Size of perforations
3/16" x 10"



