

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56064  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Mr. Gerald Casey Driller Douglas Stagle  
 Address 5484 Calienti St. Las Vegas, Nev. Address 4518 E. Vegas Vally Dr. No. 137  
 Location of well NW 1/4 SW 1/4 Sec. 26, T21 N/S, R01 E, in Clark County  
 or West of Spencer and Rawhide  
 Water will be used for Domestic Total depth of well 150 feet  
 Size of drilled hole 12" Weight of casing per linear foot 12.15 lb.  
 Thickness of casing 10 Gage Temp. of water cool  
 Diameter and length of casing 8 5/8" for 150 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure. ---  
 If nonflowing well give depth of standing water from surface 22 Ft.  
 If flowing well describe control works ---  
(Type and size of valve, etc.)  
 Date of commencement of well 6-29-65 Date of completion of well 7-8-65  
 Type of well rig Bucyrus-Erie 29 W

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	3	3	Blow Sand
3	8	5	White Clay
8	20	12	Cemented Gravel
*20	32	12	Brn Clay & Gravel & Water
32	45	13	Lt. Brn. Clay
45	50	5	Cemented Gravel
*50	55	5	Sand & gravel
55	59	4	Cemented Gravel
*59	70	11	Gravel & Water
70	85	15	Brn Clay & gravel
*85	100	15	Brn Clay, Gravel & Water
*100	150	50	Series of Clay, Gravel & Water

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)  
 from 85' to 150' ft.  
 Other aquifers 20' - 32'  
50' - 55' 59' - 70'  
85' - 100'  
100' - 150'  
 First water at 20 Ft. feet.  
 Casing perforated  
 from 50' to 150' ft.  
 Size of perforations  
1/8" x 12"

