

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56125  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in

Owner W. D. Wulfing Driller S. R. McKinney & Son  
 Address RR 1, Box 233, Las Vegas, Nev. Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: NE $\frac{1}{4}$  NE $\frac{1}{4}$  Sec. 26, T. 21N/S, R. 61E, in Clark County \_\_\_\_\_  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 140 ft.  
 Size of drilled hole 12" to 140 ft. Weight of casing per linear foot 28 lb.  
 Thickness of casing 1/4" Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 140 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 25 ft.  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Sept. 7, 1956 Date of completion of well Sept 12, 1956  
 Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	sand	
3	25	22	white clay	
25	30	5	caliche water	Chief aquifer (water-bearing formation)
30	100	70	brown clay	from <u>125</u> to <u>140</u> ft.
100	103	3	brown sand, water	Other aquifers <u>100 to 103</u>
103	125	22	brown clay	
125	140	15	red sand with sandstone streaks and water	
				First water at <u>25</u> feet.
				Casing perforated from <u>60</u> to <u>140</u> ft.
				Size of perforations <u>3/16" X 10"</u>

