

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56128  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not sign*

Owner Gert & F. Hayes Driller O. A. F. F. F.

Address Beck Drive Paradise Valley NV Address Las Vegas NV Lic. No. 105

Location of well: NW 1/4 NW 1/4 Sec. 27, T. 21, N/S, R. 6, E, in Clark County  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 110

Size of drilled hole 8 1/2 in Weight of casing per linear foot 14.6

Thickness of casing 10.6 Temp. of water \_\_\_\_\_

Diameter and length of casing 6 in C.S. 70 1/2 ft  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 15 1/2 ft

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Nov 7, 1951 Date of completion of well Nov 15, 1951

Type of well rig "71" STDY

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	9	9	SAND & GRAVEL	Chief aquifer (water-bearing formation) from <u>38</u> to <u>45</u> ft.
9	28	19	COARSE GRAVEL	
28	38	10	G&F	Other aquifers <u>75-103</u>
38	45	7	SAND & GRAVEL (water)	
45	68	23	YELLOW CLAY	
68	82	14	RED CLAY	
82	95	13	BRED SANDY CLAY	
95	103	8	SAND & GRAVEL (water)	First water at <u>45</u> feet.
103	110	7	YELLOW CLAY	

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

