Log No. 56138
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner Louis D. Hatch Driller O. A. Effinger
Address Paradise Valley Address Las Vegas Nev Lic. No. 105
Location of well: NW 1/4 NW 1/4 Sec. 27, T. 21 X/S, R 61 E, in Clark County
SE 1/4 SW 1/4
or .....
Water will be used for Domestic Total depth of well 125 FT
Size of drilled hole 10 in. Weight of casing per linear foot 12 LB
Thickness of casing 10 G. Temp. of water .....
Diameter and length of casing 8 in. OD. 100 FT.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure .....
If nonflowing well give depth of standing water from surface 18 FT.
If flowing well describe control works .....
(Type and size of valve, etc.)
Date of commencement of well July 26, 1952 Date of completion of well July 30, 1952
Type of well rig "71 Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	Sand
2	5	3	Sand & Gravel
5	12	7	Cement Gravel
12	25	13	Gravel
25	29	4	Cement Gravel
29	33	4	Gravel (water)
33	54	21	Yellow Sandy Clay
54	65	9	Red Sandy Clay
65	71	6	Gravel
71	85	14	Yellow Sandy Clay
85	94	9	Gravel (water)
94	115	21	Yellow Clay
115	119	4	Gravel (water)
119	125	6	Yellow Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 29 to 33 ft.
Other aquifers 85-94
115 - 119

First water at 33 feet.

Casing perforated
from 50 to 100 ft.

Size of perforations
1/8 in.

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8in O.D.	0	100	100	Cement 0 to 50

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)