

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56191  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in  
 Rudy

Owner Matthew & Louise Jasperica Driller Effinger Drilling & Pump Service  
 Address 4636 Paradise Rd., Las Vegas Address P.O. Box 589, City Lic. No. 212  
 Location of well: SE 1/4 SE 1/4 SW 1/4 Sec 27, T21N/S, R61 E, in Clark County  
 or 4636 Paradise Road, Las Vegas, Nevada  
 Water will be used for Domestic Total depth of well 200'  
 Size of drilled hole 60'-10" 140'-2" Weight of casing per linear foot 8"-12.50 6"-9.56  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8"-60' 6"-150'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 20 feet  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well 4/30/57 Date of completion of well 5/10/57  
 Type of well rig " 71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	4	4	Sandy Clay	
4	6	2	Cement Gravel	
6	8	2	Gravel	
8	21	13	Cement Gravel	
21	22	1	White Limestone (Water)	Chief aquifer (water-bearing formation) from <u>28</u> to <u>35</u> ft.
22	52	30	Red Sand & Clay	Other aquifers <u>21--22</u>
52	54	2	Gravel (Water)	<u>52--54</u>
54	63	14	Clay	<u>60--72</u>
63	72	4	Gravel (Water)	
72	75	3	Red Clay	
75	78	3	Yellow Clay	
78	85	7	Gravel (Water)	
85	91	6	Yellow Clay	
91	97	6	Yellow Clay & Gravel	First water at <u>21</u> feet.
97	105	8	White Clay	
105	119	14	Red Clay	
119	122	3	Red Sandstone	Casing perforated from <u>50'</u> to <u>200'</u> ft.
122	136	14	Red Clay	
136	137	1	Red Sandstone	
137	142	5	Red Clay	
142	144	2	Red Sandstone	
144	150	6	Red Clay	
150	163	13	Red Sandstone	Size of perforations <u>1/8 x 12</u>
163	165	2	Red Clay	
165	179	14	Red Sandstone	
179	181	2	Red Clay	

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
181	193	12	Red Sandstone
193	200	7	Red Clay

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	60'	60'	3 yds cement
6"	50	200'	150'	Cemented solid from 0 to 60'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.


Signed Effinger Drilling & Pump Service

Well Driller

By A. F. Effinger

License No. 212

Dated May 21, 1957



(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---