

Deeping of Well Drilled
(reworked)

**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

Log No. 56143
 Rec. _____ 19____
 Well No.
 Permit No.
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Roy Kaufman Driller Douglas Slagle

Address 548 Bell Dr. L.V. Address 4518 E. Vegas Valley Dr. Lic. No. 137

Location of well: NW 1/4 NE 1/4 Sec 27, T21 N3S, R61 E, in Clark County
 or Near Bond & Paridise Vly. Rds.

Water will be used for Domestic Total depth of well 290 Ft.

Size of drilled hole 8 " Weight of casing per linear foot 12 #

Thickness of casing 6 " X 10 gage Temp. of water Cool

Diameter and length of casing 6" linner x 220 Ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure --

If nonflowing well give depth of standing water from surface 48'

If flowing well describe control works --
(Type and size of valve, etc.)

Date of commencement of well July 27 1964 Date of completion of well August 4 1964

Type of well rig Bucyrus-Erie 29W

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
165	175	10	Fill
175	205	30	Sandy red Clay
205	220	15	Sticky Red Clay
* 220	235	15	Tight Sandy Clay & Water
235	255	20	Sticky Red Clay
* 255	285	30	Tight Sandy Clay & Water
285	290	5	Sticky Red Clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from _____ to _____ ft.

Other aquifers _____

220 to 235 Ft.

255 to 285 Ft.

First water at _____ feet.

Casing perforated

from 70 to 290 ft.

Size of perforations

1/8" x 12"

